

Outdoor Fiber Jumper



Description

Model Number	OFJ-XX-XXX-XXX-X-X
Fiber Count	1-12 Fibers
Fiber Type	Single-mode, Multi-mode
Connector Type	LC, MPO, ODC equivalent, and others
Jacket Type	Plenum, Riser
Jacket Type	Indoor/Outdoor
Construction Type	Armored, Non-Armored
Length Range	Variable lengths, (Feet or Meters)
End 1 Breakout Length	Variable lengths
End 2 Breakout Length	Variable lengths

Specification Parameter

Optical- Single-Mode	LC	MPO	ODC
Insertion Loss	≤ 0.10 dB (typ) 0.30 dB (max)	≤ 0.10 dB (typ) 0.30 dB (max)	≤ 0.25 dB (typ) 0.50 dB (max)
Return Loss	50 dB	60 dB	50 dB
Operational Wavelength	1310 / 1550 nm		
Optical- Multi-Mode	LC	MPO	ODC
Insertion Loss	≤ 0.10 dB (typ) 0.30 dB (max)	≤ 0.10 dB (typ) 0.30 dB (max)	≤ 0.25 dB (typ) 0.50 dB (max)
Return Loss	-	-	-
Operational Wavelength	850 / 1300 nm		

Performance

100% factory tested

©2022 viaPhoton, Inc. All rights reserved.