

Outdoor Hybrid Fiber Jumper



Description	
Model Number	OHFJ-XX-XXX-XXX-X-X
Fiber Count	1-4 Fibers
Fiber Type	Single-mode
Connector Type	LC, ODC equivalent, IP16, and others
# of DC Conductors on Cable	2 (red, black)
Conductor Type	14, 8, 6 AWG
Jacket Type	Riser
Jacket Type	Indoor/Outdoor
Cable Shield	Shielded Cable
UV Resistance	Yes
Length Range	Variable lengths (Feet or Meters)
End 1 Breakout Length	Variable lengths
End 2 Breakout Length	Variable lengths

Specification Parameter			
Optical- Single-Mode	LC	MPO	ODC
Insertion Loss	$\leq 0.10\text{ dB}$ (typ) 0.30 dB (max)	$\leq 0.10\text{ dB}$ (typ) 0.30 dB (max)	$\leq 0.25\text{ dB}$ (typ) 0.50 dB (max)
Return Loss	50 dB	60 dB	50 dB
Operational Wavelength	1310 / 1550 nm		
Optical- Multi-Mode	LC	MPO	ODC
Insertion Loss	$\leq 0.10\text{ dB}$ (typ) 0.30 dB (max)	$\leq 0.10\text{ dB}$ (typ) 0.30 dB (max)	$\leq 0.25\text{ dB}$ (typ) 0.50 dB (max)
Return Loss	-	-	-
Operational Wavelength	850 / 1300 nm		

Performance

100% factory tested

©2022 viaPhoton, Inc. All rights reserved.