




HyperAccess™ 24F LC Adapter Panel



Features & Benefits

- High-density adapter panel
- 24 LC connection
- Multiple applications
 - Pre-terminated LC trunks
 - Used with splice pigtails
- Supports OM4, OM5 and OS2 fiber types
- Internal shutters on LCs
- Low-loss LC connections



Description	Customer Configurator Selections
Number of Fibers	24
Fiber Mode	Customer Specified
Adapter	LC
Single-Mode Color Code	
LC Adapter	Blue
Multi-Mode Color Code	
LC Adapter	Aqua

Part numbers

SDM-24M4-AP-LC
SDM-24M5-AP-LC
SDM-24SM-AP-LC

Product Performance

Spec Parameter	Spec Value
Optical - Single-Mode	
Operational Wavelength	1310 / 1550 Nm
Insertion Loss	0.30 dB
Return Loss, LC Simplex	-55 dB
Optical - Multi-Mode	
Operational Wavelength	850 / 1300 Nm
Insertion Loss @ 850 Nm	0.30 dB
Return Loss	-25 dB
Environmental	
Installation Temp Range	0 to +70 C
Installation Temp Range	0 to +60 C
ROHS	2011 / 65 / EU

©2022 viaPhoton, Inc. All rights reserved.